

asra paints

*"Bringing Color to Life,
One Stroke at a Time"*



Naturally precious – feel good at home





ASRA PAINTS COTEX SUPERSHEEN DUST PROOF EXTERIOR EMULSION

Asra Paints Cotex SuperSheen Dust Proof Exterior Emulsion is best suited for application on walls in dry or moderately humid climatic conditions. It is an acrylic Co-Polymer, Emulsion based wall coating. Its unique formulation ensures that the product has excellent adhesion to different types of surfaces like cement plaster, asbestos etc. Asra Cotex Emulsion has a wide range of non-fading and hence longer lasting shades.

Method of Application	: Brush, Roller or Spray
Dilution	: Water Ratio 200-400ml. Per Ltr.
Drying Time	: Surface Dry 60-90 min. / Hard Dry 24-48 Hrs.
Re-Coat Tile	: At an Interval of 2-4 hours
Coating System	: 2-3 Coats as Required
Coverage	: 260-300sq.ft. per ltr. 1 Coat, 140-160sq.ft per ltr. 2 Coat

ASRA PAINTS COTEX EXTERIOR EMULSION

The Asra Paints Cotex Exterior Emulsion is ideal for wall applications in dry or moderately humid climates. It is an acrylic co-polymer emulsion-based wall coating that adheres well to various surfaces, including cement plaster, asbestos, boards, and RCC walls. Notably, it offers long-lasting shades without fading. It is a value for money product.

Method of Application	: Brush, Roller or Spray
Dilution	: Water Ratio 200-400ml. Per Ltr.
Drying Time	: Surface Dry 60-90 min. / Hard Dry 24-48 Hrs.
Re-Coat Tile	: At an Interval of 2-4 hours
Coating System	: 2-3 Coats as Required
Coverage	: 220-260sq.ft. per ltr. 1 Coat,



ASRA PAINTS COTEX WALL TEXTURE

Asra Paints Cotex Textured wall paint can give a three-dimensional look to your walls to create a unique look for your home. Asra Cotex Texture paints create a recurring type of pattern that is used to cover drywalls and ceilings to create a special appearance. Different wall paint texture types can be created according to the theme and design of your house.

Using texture paints can also help to restore the appearance of a wall that has been affected by bumps, water damage, or unevenness. Various types of texture paint can be used to complement false ceilings, create accent walls, or cover the entire wall space with textured colour. Here's a look at different wall paint texture types that you can choose for your home.

- Combing Wall Texture
- Slap Brush Texture
- Sand Swirl Texture
- Popcorn Wall Texture
- Skip Trowel Texture
- Knockdown Texture



ASRA GOLD ACRYLIC DISTEMPER

Asra Gold Acrylic Washable Distemper is a premium quality, durable, water based interior wall finish. It can be applied on ceilings and walls where a beautifying matt finish, free from irritating glares due to light reflection is desired. It is a value for money product that makes it possible for consumers to have beautiful walls at affordable prices.

Method of Application	: Brush, Roller
Dilution	: Water Ratio 500ml. Per Kg. (Acrylic Putty Done Not Dilute Water)
Drying Time	: Surface Dry 3-4 Hrs. Hard Dry 24-28 Hrs.
Re-Coat Tile	: At an Interval of 6 hours
Coating System	: 2-3 Coats as Required



ASRA PAINTS IMPEX PREMIUM ACRYLIC DISTEMPER

Asra Paints Impex Premium Acrylic Distemper Paint is a 100% water based acrylic co-polymer emulsion designed for interior walls. Available in both factory-made ready shades and in a tintable format, it gives surfaces an elegant and durable matt finish.

Method of Application	: Brush, Roller
Dilution	: Water Ratio 500ml. Per Kg. (Acrylic Putty Done Not Dilute Water)
Drying Time	: Surface Dry 3-4 Hrs. Hard Dry 24-28 Hrs.
Re-Coat Tile	: At an Interval of 6 hours
Coating System	: 2-3 Coats as Required



ASRA COTEX EPOXY GROUT

STAIN FREE JOINT EPOXY FLOOR 'N' WALL

PRODUCT DESCRIPTION

Asra Cotex is a stain free color-fast chemical resistant, 100% solid Epoxy Grout for ceramic tile, vitrified tile marble and stone.

APPLICATION

Asra Cotex is ideally suited for residential and commercial installations where material must-resist physical abuse. Shock and chemical exposure.

- Easy to Apply & Clean
- Anti-Fungal & Anti-Bacteria
- Color Fast & 10% Stain Free
- Available in Range of Colours
- Acid/Chemical Resistant
- For Floor and Wall Surface





ASRA PAINTS COTEX EXTERIOR WALL PRIMER

Asra Paints Cotex Exterior Wall Primer is water based Acrylic Co-polymer Emulsion which can be applied over a variety of exterior walls, ceiling made of Sand, Cement Plaster, Asbestos, Cement, Brick, Lime or Pre-Painted surfaces, P.O.P etc. Exterior Water Base Primer is fast drying & provides excellent hiding, holdout and spatter less application. Recommended for interior dry wall, plaster & masonry surface. It can be used for priming new or previously painted exterior cementitious surfaces.

COVERAGE	COLOR AVAILABLE	DRYING TIME	WATER BASED
On Smooth Masonry Surface by Brushing 1 Coat 215-270 sq.ft. / Ltr.	White* Please Note: Enquire Wall Primer is under coat.	20 MINS	

ASRA PAINTS NEO BHARAT LATEX PLASTIC PAINT

Asra Paints NEO BHARAT Latex Plastic Paint is ideal for wall applications in dry or moderately humid climates. It is an acrylic co-polymer emulsion-based wall coating that adheres well to various surfaces, including cement plaster, asbestos, boards, and RCC walls. Notably, it offers long-lasting shades without fading. It is a value for money product.

Method of Application	: Brush, Roller or Spray
Dilution	: Water Ratio 200-400ml. Per Ltr.
Drying Time	: Surface Dry 60-90 min. / Hard Dry 24-48 Hrs.
Re-Coat Time	: At an Interval of 2-4 hours
Coating System	: 2-3 Coats as Required
Coverage	: 220-260sq.ft. per ltr. 1 Coat,



ASRA PAINTS 24 CARAT METALLIC GOLD PAINT

Asra Paints 24 Carat Metallic Finish Luxury Emulsion provides opulent shimmer to any living space. When applied in a single colour, This luxurious finish makes a bold stylish statement & a sparkling appearance to your walls. It may be combined with special effect techniques such as Ragging, Combing, Dragging etc. to give an Elegant Texture to your Dream Home.

Method of Application	: Brush, Roller or Spray
Dilution	: Water Ratio 200-400ml. Per Ltr.
Drying Time	: Surface Dry 60-90 min. / Hard Dry 24-48 Hrs.
Re-Coat Time	: At an Interval of 2-4 hours
Coating System	: 2-3 Coats as Required
Coverage	: 260-300sq.ft. per ltr. 1 Coat, 140-160sq.ft per ltr. 2 Coat

ASRA COTEX HI-GLOSS SYNTHETIC ENAMEL

Asra Cotex Hi-Gloss Synthetic Enamel that provides excellent weather resistance. It is especially formulated to give a tough and fungus free finishes with excellent gloss and color retention. Asra Paints is widely used on Interior and Exterior building surfaces made of wood, metal and masonry. It forms a tough film that is highly resistant to household stains. It thereby serves as a protective armour around the painted surface.

Method of Application	: Brush, Spray
Dilution	: Water Ratio 200-400ml. Per Ltr.
Drying Time	: Surface Dry 60-90 min. / Hard Dry 24-48 Hrs.
Re-Coat Time	: At an Interval of 2-4 hours
Coating System	: 2-3 Coats as Required
Coverage	: 215-270sq.ft. per ltr.



ASRA PAINTS GUNGUN RED OXIDE PRIMER

Asra Paints Gungun Red Oxide Primer is an economical coating used on metal surfaces due to its excellent adhesion and anti-corrosive properties. Endowed with easy flow technology, leveling and excellent brushability, it gives uniform coverage to the surface. It is free from heavy metals like lead, mercury and chromium.

Method of Application	: Brush, Spray
Dilution	: Water Ratio 200-400ml. Per Ltr.
Drying Time	: Surface Dry 60-90 min. / Hard Dry 24-48 Hrs.
Re-Coat Time	: At an Interval of 2-4 hours
Coating System	: 2-3 Coats as Required
Coverage	: 215-270sq.ft. per ltr.



ASRA PAINTS NO.1 ALUMINIUM PAINT

Asra Paints Aluminium Paint is a dual pack general purpose aluminium paint having very good lustre. It gives a protective metallic finish, designed to be used on well prepared metal surfaces like storage tanks, roofs and pipe work. The paint film reflects heat and light while also protecting from corrosion due to its water permeable nature.

Do not thin the paint. Mix medium & paste thoroughly keep out of reach of children.

Method of Application	: Brush, Spray
Drying Time	: Surface Dry 60-90 min.
Re-Coat Time	: At an Interval of 2-4 hours
Coating System	: 2-3 Coats as Required
Coverage	: 180-200sq.ft. per ltr.
Solid	: 50%
Viscosity	: 20-25 sec@ 30° by ford cup





ASRA INDUSTRY

A-2/29, G.D. Steel Compound, Sahibabad Industrial Area,
Site-4, Sahibabad, Ghaziabad-201010 (U.P)

FOR INQUIRIES AND FEEDBACK:

E-mail: contact@asrapaints.com, Call: +91-99993 64799, 9717916516

